680301

DIESEL METER WITH MECHANICAL 4 DIGIT REGISTER, 100 L/MIN

Nutating-disk meter for diesel with mechanical register. Very low pressure drop; it can be used for gravity fed applications. Resetable partial reading up to 999,9 litres and permanent 6 digit totaliser. 1" BSP (F) inlet and outlet, both with flange for optional flange mounting. The meter allows to orientate the inlet and outlet in four different positions.

DATOS TÉCNICOS

Accuracy	0.01
Flow range	20 - 100 l/min (5.28 - 26.4 gal/min)
Fluid inlet	1/2" BSP (F)
Fluid outlet	1/2" BSP (F)
Fluids	Diesel
Maximum free flow delivery	100 l/min (26.4 gal/min)
Maximum outlet pressure	10 bar (145 psi)
Meter	MECHANICAL
Metric	LITRES
Operating Temperature Range	-10 - 60 °C (14 - 140 °F)
Pulses per litre	10
Weight	2.27 kg (5 lb)
Wetted materials	Technopolymer, Aluminium

DOCUMENTACIÓN

NOMBRE	DESCRIPCIÓN
868811.pdf	Instructions manual 1

SAMOA Industrial, S.A.
Pol. Ind. Porceyo, I-14 · Camino del Fontán, 831 · 33392 Gijón - España
Tel.: (+34) 985 381 488 - Fax: (+34) 985 384 163
info@samoaindustrial.com
www.samoaindustrial.com