## Harlequín<sup>®</sup> StorageTanks

**RELIABLE CONTAINERS** 

## Harlequin 5400ITT Bunded Fuel Tank



## **Tank Dimensions:**

- Diameter: 2575mm
- Overall Height: 2100mm
- Brimful Capacity: 5307L
- Nominal Capacity: 5042L
- Net Weight: 325kg

Harlequin 5400ITT bunded top offtake oil tanks come equipped with a range of standard fittings, including an Ecoflex top offtake fitting and ultrasonic contents gauge – the safest and most complete solution for a fully compliant installation.

## **Standard Features:**

- Moulded from durable medium density polyethylene material
- Integrally bunded
- Ecoflex top offtake fitting
- 16" lockable access lid
- 2" BSP(M) offset fill point
- Overfill prevention valve
- 4" lockable inspection cap
- Ultrasonic contents gauge with remote display
- LRC overfill prevention probe
- Bund monitor
- Inner tank vent

Issued By: Harlequin Manufacturing Limited 21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 OPB T: +44 (0)28 9261 1077 W: www.harlequin-mfg.com E: info@harlequin-mfg.com

Doc Ref: TL149b Issue: 01 Revision 02