Harlequin[®] torageTanks

Harlequin 2525ITT **Bunded Fuel Tank**

RELIABLE CONTAINERS

Tank Dimensions:

Length: 2450mm Width: 1200mm

Overall Height: 1685mm Brimful Capacity: 2550L Nominal Capacity: 2422L

Net Weight: 235kg



Harlequin ITT bunded top offtake oil tanks come equipped with a range of standard fittings, including an Atkinson Tanktop and ultrasonic contents gauge the safest and most complete solution for a fully compliant installation.

Standard Features:

- Moulded from durable medium density polyethylene material
- Integrally bunded
- Atkinson Tanktop top offtake fitting (c/w integral anti-siphon valve, non-return valve, 50Mic filter & priming button)
- 16" lockable access lid
- 2" BSP(M) fill point
- 4" lockable inspection cap
- Ultrasonic contents gauge with remote display
- LRC overfill prevention probe
- Inner tank vent
- Moulded-in handles and slinging points for ease of lifting

Issued By:

Harlequin Manufacturing Limited 21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 OPB

T: +44 (0)28 9261 1077 W: www.harlequin-mfg.com E: info@harlequin-mfg.com

Doc Ref: TL257c Issue Date: July 2020 Issue: 01 Revision 00

Auth: JC